

Alternative energy projects and Therminol technical services A powerful combination

Eastman Therminol® heat transfer fluids are being selected in alternative energy projects because of their excellent, proven performance over a wide temperature range in related applications. For decades, Therminol heat transfer fluids have been used in conventional natural gas processing applications. With the creation of an abundance of new projects to harness alternative energy sources, the use of Therminol fluid has expanded to projects involving biofuels, cogeneration, nanotechnology, oil sands, and solar energy. These alternative energy projects share a common theme—the energy they harness is no longer based on traditional petroleum or nuclear-based sources. Instead, the energy involved in these projects is from resources such as waste heat, renewables, and nature itself. This report will discuss how Pristine Power Inc., EnPower Green Energy Generation Limited Partnership, and Chinook Engineering partnered with the Therminol technical service team to solve a green energy initiative challenge put forth by emerging governmental regulation.

In 2002, the Canadian province of British Columbia (BC) passed a clean energy act that required a major power producer, BC Hydro, to meet 50% of its new power needs from renewable sources and cogeneration. In 2007, the province increased the clean energy requirement to 90%. This is an example of a government initiative to spur the development of energy alternatives that has met with success in British Columbia. A company that has seen this initiative as an opportunity to employ its expertise is Pristine Power Inc. of Calgary, Alberta (AB).

Pristine Power is in the business of developing, owning, and operating independent power plants that will produce and sell electricity and, in some cases, sell process steam to industrial users. Pristine Power and ENMAX Green Power Inc. announced in September 2008 that commercial operations have started at their jointly owned EnPower Energy Recovery Generation (ERG®) projects in British Columbia under the terms of a 20-year electricity purchase agreement with BC Hydro. These new plants convert waste heat from the gas pipeline into electricity. Their two BC plants will produce a total of 10 MW of clean energy and offset 25,000 tonnes of greenhouse gases (GHG) annually.

The first plant, located in Savona, BC, generates electricity from waste heat created by existing gas compressors on Spectra Energy's main natural gas pipeline. The ERG process starts by transferring the waste heat to Therminol heat transfer fluid. The hot Therminol fluid

is then used to vaporize a separate working fluid which is used in an organic Rankine cycle for power generation. ERG projects use proven technologies, and similar systems are used on pipeline compressors and in geothermal applications around the world. The Savona project is the first of two EnPower 5-MW projects in the province. The other 5-MW project on the same pipeline at 150 Mile House, BC, began operations in October 2008.

EnPower was formed by its owners to manage the projects for waste heat recovery in Western Canada and was responsible for the construction of the 5-MW cogeneration projects at 150 Mile House and Savona, BC. Chinook Engineering Ltd. of Vancouver, BC, was commissioned by EnPower to provide the engineering design for these projects. The challenge that confronted Chinook Engineering was finding a heat transfer fluid that has a proven track record and could meet performance requirements and be used in a low-pressure system. Randy Bohl, mechanical engineer at Chinook Engineering, was assigned the task of finding such a heat transfer fluid.

Early in the process, Bohl contacted the Therminol technical service team for assistance on information regarding heat transfer fluids. He discussed his needs with Ravi Prakash, senior Therminol technical service specialist, thus embarking on a long-term relationship from the initial stages of the project through construction and to start-up of the heat transfer fluid system. "There were important yet simple lessons to be learned from this relationship and the initiative on behalf of Chinook Engineering that could benefit many engineering companies on their projects," Prakash said. "The important starting point is that Bohl contacted us early in the process so we could assist with a thorough design review of their system. Sometimes we are consulted after the fact, and important criteria for a well-designed system may be overlooked. So, we request engineering companies to contact us early should they think they may need our advice. Fortunately in this case, Bohl got us involved nearly from the beginning, avoiding many of the design pitfalls that can happen." This guidance, offered at no additional charge by the Therminol technical services team, is a vital part of the TLC Total Lifecycle Care® program. "In addition to the design review, we also have a toll-free technical services hotline that is available to handle inquiries on a routine basis. For the EnPower project, we also provided a comprehensive engineering seminar at Chinook that was created with the needs of the design engineer in mind. We then followed up with an on-site training seminar at Spectra, the end user, which focused on the safe use, operation, and maintenance of its new Therminol heat transfer fluid system."

Brad McCann, national market manager for Therminol heat transfer fluids in Canada, echoes the sentiment of Prakash: "We have 50 years of experience in the use of Therminol heat transfer fluids with thousands of systems worldwide. We use Therminol fluids in our own manufacturing facilities." McCann was responsible for the commercial coordination of the services and product offerings to Pristine/EnPower, Chinook, and Spectra. He adds, "We are willing to share this experience with all stakeholders for projects involving Therminol heat transfer fluid. That experience extends not only from project conception to design and to construction but also to the end users. We offer the end user an unparalleled technical support program that provides start-up assistance, operator training, sample analysis, and troubleshooting assistance. Although we have assisted customers with conversions of existing systems to Therminol products from other fluids, the key to success for new system designers is to contact the experienced engineers at Therminol technical services in the conception stage to help ensure that the system is well designed. We can then offer training to the end user to help ensure the well-designed system is also well operated and well maintained."

Mike Rekrutiak, project manager for EnPower Green Energy Generation, supports McCann's comments regarding the technical services offered by the Therminol team during the early stages of project design. Rekrutiak states, "We had some special needs for a low-pressure system at Savona and were in the beginning phase of several new projects on the Spectra Energy natural gas pipeline in British Columbia. The Therminol engineering team understood our concerns and suggested

Therminol 55 for these projects that met the low-pressure requirement as well as our performance needs. Also, the Therminol commercial team was helpful ensuring on-time deliveries of Therminol fluid to these locations. We are pleased with the technical and commercial support we have received from Team Therminol and would not hesitate to recommend their service for our future projects and to other project management and engineering firms."

Prakash says, "We have worked with thousands of satisfied customers worldwide for many, many years. While we realize that the typical components of heat transfer systems are often similar, each system is still unique and requires care and attention since the differences may be in the details—the same details that may get overlooked. The benefits from working with an experienced heat transfer fluid technical services team in the project design phase are clear. Beginning with a well-designed system results in safer operation, more efficient start-ups, and better on-stream time and requires less energy and less heat transfer fluid in the long term."

McCann concludes, "We see many benefits coming from the influx of energy-related projects in which we have been involved and encourage prospective project managers and engineering firms to contact the engineers in the technical services group in the early stages of these projects. I believe that the proactive efforts of alternative energy companies, such as Pristine/EnPower, Chinook Engineering, and Spectra, contacting us in the conception stage will benefit their generation projects for many years to come."

For more information, or to find the sales or technical contact nearest you, visit the "Contact us" page on our website: www.therminol.com.

North America Solutia Inc. A subsidiary of Eastman Chemical Company 575 Maryville Centre Drive St. Louis, MO 63141 U.S.A.

Telephone: Customer Service, 800-426-2463 Technical Service, 800-433-6997 Fax: Customer Service, (1) 314-674-7433 Latin America Solutia Brasil Ltda. A subsidiary of Eastman Chemical Company Rua Alexandre Dumas, 1711—Birmann 12— 7° Andar 04717-004 São Paulo, SP, Brazil

Telephone: Brazil, 0800 55 9989 Other Locations, +55 11 3579 1800 Fax: +55 11 3579 1833 Europe/Middle East/Africa Solutia Europe SPRL/BVBA A subsidiary of Eastman Chemical Company Corporate Village—Aramis Building Leonardo Da Vincilaan 1 1935 Zaventem, Belgium

Telephone: +32 2 746 5000 Fax: +32 2 746 5700 Asia Pacific
Eastman (Shanghai) Chemical
Commercial Company Ltd.
Building 3, Yaxin Science & Technology Park
Lane 399 Shengxia Road
Pudong New District
201210, Shanghai, P.R. China

Telephone: +86 21 6120 8700 Fax: +86 21 5027 9229

EASTMAN

The results of insight

Eastman Chemical Company Corporate Headquarters P.O. Box 431

P.O. Box 431 Kingsport, TN 37662-5280 U.S.A.

U.S.A. and Canada, 800-EASTMAN (800-327-8626) Other Locations, +(1) 423-229-2000

www.eastman.com/locations

Although the information and recommendations set forth herein are presented in good faith, Eastman Chemical Company and its subsidiaries make no representations or warranties as to the completeness or accuracy thereof. You must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the health and safety of your employees and purchasers of your products. Nothing contained herein is to be construed as a recommendation to use any product, process, equipment, or formulation in conflict with any patent, and we make no representations or warranties, express or implied, that the use thereof will not infringe any patent. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS AND NOTHING HEREIN WAIVES ANY OF THE SELLER'S CONDITIONS OF SALE.

Safety Data Sheets providing safety precautions that should be observed when handling and storing our products are available online or by request. You should obtain and review available material safety information before handling our products. If any materials mentioned are not our products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

© 2015 Eastman Chemical Company. Eastman brands referenced herein are trademarks of Eastman Chemical Company or one of its subsidiaries. The ® used on Eastman brands denotes registered trademark status in the U.S.; marks may also be registered internationally. Other companies' brands referenced herein are trademarks of their respective owners.